


Merica Series-MPI50

Probe

MPI-50-H-5.5G



Technical Specifications


Recommended Minimum Center	:1.27mm(50mil)
Current Rating	:3amps, continuous
Contact Resistance	:60milliohms
Mounting Holes Size	:Φ1.0
Full Stroke	: 6.35mm
Rated Stroke	:4.30mm
Spring Force	:150gf(5.5 oz)

Materials

Receptacle	:Bronze, Gold Plated
Contact Barrel	:Bronze, Gold Plated
Spring	:Music Wire, Gold Plated
Plunger	:BeCu or Steel, Rhodium Plated or Gold Plated

Receptacle

RI-50-CR



RI-50-SC



RI-50-CRW




RI-50-SW




Tip Styles


Test Centers-50mil(1.27mm)




MPI-50-B



MPI-50-K5




MPI-50-G



MPI-50-J




MPI-50-F



MPI-50-T5




MPI-50-U




MPI-50-C




MPI-50-H




MPI-50-BK



MPI-50-H5



MPI-50-S5



MPI-50-F

How To Order: Spring Contact Probe

MPI-50 H 5.5 G
 Series Tip Style Spring Force (oz) Plating Options [G-Gold Plated]

Series: MPI-50
 Tip Style: B, K5, G, J
 Spring Force: 5.5 oz

Receptacle

RI-50 CRW
 Series Terminations

Terminations: CRW